

Dry Core Drilling

ESD 162 Dry Core Drill

NEW Powerful Innovation in Drilling Reinforced Concrete!

• IHT soft impact technology provides faster drilling, reduced heat, extended bit life, & excellent dust extraction.



- Dry drilling up to 8" in brick/ block, 6-3/8" in reinforced concrete.
- New technology to replace the need for water in reinforced concrete; no slurry!
- Can be used for hand or rig-guided drilling.
- Dust extraction system for increased user safety.

Ergonomic design & anti-vibration handles



The ESD 162 comes with the EDMC Pro digital motor control with a service and overload indicator, soft start, & over current cut-off.

Kits Available:

Anchor Stand Kit: Part No. ESD 162 POSA





Specifications		
Motor Power	19.5 Amp, 110 V	
Load Speeds (RPM)	0-1000 RPM	
Drilling Diameter	6-3/8" / 8"	
Spindle Connection	1-1/4" x 7 UNC 5/8" x 11 UNC	
Collar Diameter	60 mm	
Weight	15 lbs (motor only)	



Dry Core Drilling

ESD 162 Accessories

Core Bits are a Truly Unique Product, Specially Designed for the ESD 162 Dry Core Drill.

PB core bits MUST be used when in hammer mode.

- Optimal results in rebar reinforced concrete, brick, block, & more.
- Maintain high working speeds during extended drilling periods.
- Highly durable diamond segments.
- Extremely cool cutting & superior dust collection.





Centering Rod for starting the holes free hand - part no. 36394000



ESD 162 & BST 162 H Stand Kit: Part # ESD 162 POSA

Part No.	Diameter
PB1341334	1-3/4"
PB2001334	2"
PB2121334	2-1/2"
PB3001334	3"
PB3121334	3-1/2"
PB4001334	4"
PB4121334	4-1/2"
PB5001334	5"
PB6001334	6"
PB6381334	6-3/8"
PB7001334	7"
PB8001334	8"

Distributed By:



22 Harbor Ave, Norwalk, CT 06850 4330 Center St, Deer Park, TX 77536 Phone 800-700-5919 • 203-853-9522 info@csunitec.com • www.csunitec.com